



CONDO KANDY



**LUXURY
OUTDOOR
PORCELAIN
PAVERS
SPECIFICATIONS**



PORCELAIN PAVERS

COMPOSITION & MANUFACTURE

Porcelain pavers are created by baking a mixture of clay, sand and other minerals. These are then baked into a high-temperature kiln. From this, an incredibly durable and non-porous material is created; known as porcelain paving.

PERFORMANCE & MAINTENANCE

- Non-absorbent (water absorption is less than 0.1 percent)
- Quick and easy to install
- Easily dismantled, renewable and reusable
- Frost Resistant | Fire Resistant | Salt Resistant | Mold Resistant | Stain & Fade Resistant | Impact Resistant
- High breaking strength
- Easy to clean, can be cleaned with water, broom/mop & dish soap
- Resistant to thermal shock
- Resistance to Algae and Pesticides.
- Anti-slip surface (R11)

INSTALLATION

Our porcelain pavers can be installed using low profile pedestals, as low as 1/8 inch. While providing adequate room for drainage, this will also provide the tightest fit to the surface below, resulting in a total floor lift of less than 1 inch, which are perfect for condo balconies, where door thresholds and railing height bylaws are a concern. For higher lift requirements, adjustable height pedestals can be used. Our porcelain pavers can be installed on uneven membrane roofs, condo balconies, terraces and traditional backyard decks.

SPECIFICATIONS

Tile Dimensions: 24x24"x3/4"H

Details	QTY	Square Ft.	Weight (lbs)
Per tile	1	4	34.39
Per Box	2	8	68.78
Per Pallet	64	248	2,315

Pallet dimensions: 31 1/2" x 47 5/8" x 29 1/2"

